

For the Extension of any USB Keyboard and Mouse, Stereo Audio, DVI-D and RS-232 Signals up to 15 Kilometers

FEATURES

- Top Signal Quality at Maximum Extension Over Singlemode Fiber (15 Km)
- Superior Image Quality at all Resolutions
- Video Resolutions up to 1920 x 1200 at 60Hz (1280 x 1024 at 75Hz)
- Customizable/Programmable DDC Table
- Supports USB Keyboard/Mouse
- Touch Screen Compatible
- Supports Stereo Audio
- Supports DVI-D
- Supports RS-232 Control from 300bps to 115,000bps
- Supports all USB Keyboards Fully Transparent
- Fiber Plug Type LC, Singlemode
- Compatible With all Operating Systems

APPLICATIONS

- Corporate or Educational Presentations
- Financial (Remote Servers/User Control)
- Call Centers
- Industrial (Long-Range Workstation Isolation)
- Information Terminals/Kiosks
- Airport Installations
 (Air Traffic Control/Passenger Information)
- KVM Extension where Exceptional Quality of Signal is Crucial
- Medical (Remote Operation Away from Sensitive/ Magnestic Equipment)
- Recording (for Large Studios where Editing/Mixing Stations are Compact and/or Require Complete Silence)









OVERVIEW


The FDX-3500 consists of a transmitter and receiver that extend KVM, DVI-D, audio and RS-232 signals. It is a professional quality KVM capable of extending signals up to 15 Kilometers over a single singlemode fiber optic cable.

APPLICATION DIAGRAM



Application Diagram

Fiber Optic Cable up to 15 Kilometers





FDX-3500 Front



FDX-3500 Rear

VIDEO	
Input Interface	DVI-D Female (Single-Link)
Resolution	1920x1200 at 60Hz
DDC	Internal Table can be Re-programmed
Audio	
Signal Type	Stereo Audio
Bandwidth	15MHz, OdB
Impedance	10K Ohm
Connector	3.5mm Stereo Mini Female
Audio	
Signal Type	Stereo Audio
Bandwidth	15MHz, OdB
Impedance	10K Ohm
Connector	3.5mm Stereo Mini Female

Other	
RS-232	Data up to 115,000bps
USB	USB Keyboard and Mouse Compliant
Fiber Extender	Duplex LC Connector Eye Safety Designed to meet Laser Class 1 comply with EN60825-1 Operates at a nominal wavelength of 1310nm Distance 15km 1310nm FP
Dimensions	4.5"x5.5"x1.70"
Weight	8 Lbs.

ORDERING INFORMATION	
Part No.	Description
FDX-TX3500	FDX-3500 Sinlgemode Transmitter
FDX-RX3500	FDX-3500 Singlemode Receiver
PS5VDC4A	(2) Power Supply 5V 4A



Designed and Manufactured in the USA

