

DVI-D Extender up to 50 ft. **Over DVI Cable**

DVX-100

DVI-D Extender Over DVI-D Cable

Extend DVI-D connections to computer monitors or projectors up to 50 ft.

OVERVIEW

The DVX-100 extends the distance between any computer using DVI-D to connect to monitors or projectors up to 50 feet The system features daisy chain capabilities that can extend the limit up to 100 feet using DVI-D Cables.

FEATURES

- Supports MAC and PC DVI-D
- Extends DVI-D signals up to 50 feet and up to 100 feet when daisy chained
- Resolution up to 1920 x 1080
- No pixel loss
- Maintains the highest DVI single link video resolution
- DVI output regenerates TMDS digital video
- External power supply

APPLICATIONS

Presentations

DVX-100 enhances any presentation from commercial products to corporate financial data. It can be used in show rooms, board rooms, trade shows and window displays.


Data Broadcasting

Data - such as news, stock prices, sports results, and flight information - can be broadcast in real time to various monitors and/or speakers.

Learning and Training

DVX-100 can be used in educational presentations to multiple locations, in schools and in other training facilities.

APPLICATION DIAGRAM



- Provides noiseless operating environment at the remote station
- Places CPU outside of harsh environment
- Saves space on your desktop

SPECIFICATIONS





AUDIO VIDEO |

NNOVATION

DVX100 Front

| VIDEO | DEO | | |
|--------------------------|----------------------------------|--|--|
| Format | DVI-D Single Link | | |
| Maximum Pixel Clock | 165 MHz | | |
| Input Interface (TX) | (1) DVI-D 29-pin female | | |
| Output Interface (RX) | (1) DVI-D 29-pin female | | |
| Resolution | Up to 1920 x 1200 @ 60Hz | | |
| DDC | 5 volts p-p(TTL) | | |
| Input Equalization | Automatic | | |
| Input Cable Length | Up to 20 ft. | | |
| Output Cable Length | Up to 20 ft. | | |
| OTHER | | | |
| Power | External 5VDA 1A, 2A | | |
| Dimensions | 2.75 in W x 0.08 in H x 3.4 in D | | |
| Weight | 0.20 lb | | |
| Operating Temp. | 0-55 °C (32-131°F) | | |
| Storage Temp. | -20-85 °C (-4-185 °F) | | |
| Humidity | Up to 95% | | |

| Part No. | Description |
|----------|---|
| DVX-100S | Active DVI Repeater Male/Female 50'. Includes: [DVX100 & (PS5VD2A)] |
| DVX-PRXS | Active DVI Learner Programmer for EDID '. Includes: [DVX-PR1 & (PS5VD2A)] |

Many leading companies have recognized and embraced the innovation of SmartAVI's technologies and have successfully incorporated them into their organizations. Users of SmartAVI include:



Designed and Manufactured in the USA

www.smartavi.com Tel: 800.AVI.2131 • 818.503.6200 • 11651 Vanowen St. North Hollywood, CA. 91605