



P2P-KDR300

Point-to-Point Single-Head DisplayPort CAT5 & Fiber Receiver with USB 2.0 and Audio

Extend, control, and manage your DP-based workstation over IP with the P2P-KDR300. Supporting flexible Direct, Matrix, and SaviGate modes, the P2P-KDR300 adapts to your installation needs — from simple point-to-point extensions to full multi-user managed environments — over CAT5 or Fiber.

FEATURES



Supports DP video up to 4K @ 30Hz



Transparent USB 2.0 extension for peripherals



Analog audio passthrough



Selectable Direct, Matrix, and SaviGate modes via web interface



SaviGate Gateway support for centralized management (sold separately)



Up to 100m over CATx / 10km over fiber



Ultra-low latency JPEG2000 compression



Plug-and-play installation



EDID learning and management

IDEAL USE CASES



AV and IT extension for secure environments



Digital signage and workspace centralization



Medical and industrial command centers



Military and government operations



Broadcast and production control rooms

HOW IT WORKS

Flexible KVM extension and switching

The P2P-KHR310 can operate in multiple modes depending on your application needs:



Direct Mode

Simple point-to-point extension without configuration

Supports: 1 Transmitter / 1 Receiver



Matrix Mode

OSD-based multi-user KVM switching across a network

Supports: Up to 64 Transmitters / 8 Receivers




SaviGate Mode

Centralized management, access control, and advanced routing when integrated with a SaviGate controller

Supports: Up to 128 Transmitters / 16 Receivers

Modes are easily changed using a simple dropdown menu within the web browser interface of each unit.



COMPATIBLE TRANSMITTERS

Pairs with the following transmitter models for point-to-point operation:

- **P2P-KVT300** - DVI Transmitter via CATx & Fiber
- **P2P-KHT300** - HDMI Transmitter via CATx & Fiber
- **P2P-KDT300** - DisplayPort Transmitter via CATx & Fiber

SPECIFICATIONS

Video OUT	
Format	DisplayPort1.2 Compliant, Video Bandwidth up to 17.28 Gbps
Video Resolution	Up to 4K @ 30 Hz
Connector	(1) DisplayPort (20-Pin female)

System	
Interface	EDID Storage & Emulation
Transmission Distance	CAT5: Up to 100 m; LC Connector Fiber Multimode: Up to 500 m; Fiber Single Mode: Up to 10 km
Compression	Ultra-Low Latency JPEG2000
Management	Selectable Direct, Matrix, SaviGate Gateway support for centralized management (sold separately)

Audio	
Format	PCM 2.0/2.1/5.1/7.1, Dolby Digital 5.1 ch, Dolby Digital Plus, Dolby TrueHD, DTS 5.1 ch
In/Output Interface	3.5 mm Stereo Aux Socket (female)

USB	
Output Interface	(4) USB Type A, USB 2.0, USB 1.1, USB 1.0 compatible
KM	Keyboard & Mouse Emulation

Other	
Power	12 V DC, 3 A (Power Supply Included)
Reliability (MTBF)	135,540 Hours (MIL-HDBK-217F (N2) Parts Count Prediction Calculator)
Environmental Operating Temperature	0°C to 45°C (32°F to 113°F)
Environmental Operating Humidity	10% to 90%, non-condensing
ESD Protection	Protection per IEC 61000-4-2 Standard at ±30 kV Air and ±30 kV Contact
Support Warranty	1-Year
Certification	CE, FCC, RCM, UL
Dimensions	9.5"W x 5.25"D x 1.7"H
Weight	1 lbs 0.45 kg

ORDERING DETAILS

P2P-KDR300-S	Point-to-point Single-Head DisplayPort CAT5 & Fiber Receiver with USB 2.0 and Audio. [P2P-KDR300, PS5VD3A]
--------------	--